

537, 673

Rec'd PCT/PTO 06 JUN 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

10/537673

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
24 June 2004 (24.06.2004)

PCT

(10) International Publication Number
WO 2004/054236 A1

(51) International Patent Classification⁷: H04N 3/233,
3/223

(72) Inventor; and

(75) Inventor/Applicant (for US only): DE PAUW, Adriaan,
Philippe, Digna [NL/US]; 1109 McKay Drive, M/S-41SJ,
San Jose, CA 95131 (US).

(21) International Application Number:
PCT/IB2003/005606

(22) International Filing Date: 3 December 2003 (03.12.2003)

(74) Common Representative: KONINKLIJKE PHILIPS
ELECTRONICS N.V.; c/o LESTER, Shannon, 1109
McKay Drive, M/S-41SJ, San Jose, CA 95131 (US).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/431,344 6 December 2002 (06.12.2002) US

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(71) Applicant (for all designated States except US): KONIN-
KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(84) Designated States (regional): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,

(71) Applicant (for AE only): U.S. PHILIPS CORPORA-
TION [US/US]; 1251 Avenue of the Americas, New York,
NY 10510-8001 (US).

[Continued on next page]

(54) Title: DRIVE APPARATUS FOR FRAME DEFLECTION AND METHOD



(57) Abstract: A frame drive circuit for a CRT device having a deflection processor (14) which develops a deflection processor output signal includes a frame coil (16) having a first core half (12) and a second core half (18), and a first driver (20) and a second driver (22). The deflection processor output signal is applied to each of the first driver (20) and the second driver (22). Each of the first driver (20) and the second driver (22) are selectively operative independently of each other to develop respectively a first coil drive signal (24 OUT) and a second coil drive signal (26 OUT) as a function of the deflection processor output signal. The first coil drive signal (24 OUT) and the second coil drive signal (26 OUT) are applied to a respective one of the first coil half (12) and said second coil half (18).

WO 2004/054236 A1



SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Declaration under Rule 4.17:

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent*

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.